

### PLM-820 STREET MARKING PAINT

#### DESCRIPTION

- PLM-820 is a high-quality street marking paint.
- It provides maximum brilliance and is highly reflective.

#### FEATURES

- Long wearing
- Highly reflective
- No “pick up” from vehicles driving over it when applied properly
- Longer drying time will result in greater resistance and durability
- Available in red, white, black, yellow and handicap blue
- Solvent based

#### DIRECTIONS FOR USE

- The application surface must be free of debris, clean, dry and in sound condition.
- Use a low-speed power agitator to mix the paint thoroughly to a uniform consistency.
  - Storage of this product in cold or freezing temperatures may cause it to thicken or separate. This will not harm its performance.
  - Before using, allow to warm to room temperature and mix thoroughly.
- Thinning depends on the method of application and the type of equipment being used.
  - The material should be used in its original form to start.
  - If it does not flow freely, add one pint of V. M. & P. naphtha per gal. of PLM-802.
- Apply the paint evenly at the recommended film thickness and spreading rate.
  - Wet film thickness – 15.0 mils.
  - Dry film thickness – 7.5 mils.
  - 320 linear ft. of standard 4 in. wide stripe
- PLM-820 can be applied using airless spray line striping equipment or conventional spray line striping equipment for larger areas and a brush or roller for smaller applications.
- Drying time at 15 mils. wet is as follows:
  - Dry to touch – 60 minutes
  - Dry for no traffic “pick up” – 60 minutes

#### SPECIFICATIONS

<b>Components</b>	Street Making Paint
<b>Product</b>	Paint
<b>Physical Form</b>	Liquid
<b>Color</b>	Pigmented
<b>Odor</b>	Paint
<b>Specific Gravity</b>	1.29
<b>Flash Point (TCC)</b>	65F°

### WARNINGS AND CAUTION

- Keep out of the reach of children.
- Always wear safety glasses when handling this product.
- If the product makes contact with eyes, flush eyes thoroughly with water lifting eyelids to ensure complete irrigation. Remove contact lenses if applicable. Seek medical attention.
- If the product makes contact with skin, flush contact area with water then wash with soap and water. If skin irritation persists, seek medical attention.
- Contaminated clothing should be laundered before reuse.
- Be sure the application area is well ventilated. If fumes become concentrated, move to an area of fresh air. If breathing is affected, seek medical attention.
- If appreciable amounts of the product are ingested, seek medical attention.
- Refer to the Safety Data Sheet (SDS) for detailed emergency procedures, precautionary measures and handling instructions.